SAFETY DATA SHEET
LIFT RTU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name LIFT RTU

Product number A129 EV

Internal identification Janitorial

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Heavy Duty, Alkaline Liquid Hard Surface Cleaner.

1.3. Details of the supplier of the safety data sheet

Supplier

UK Supplier:
Evans Vanodine International plc
Brierley Road,
Walton Summit,
Preston. UK. PR5 8AH
Tel: 01772 322 200
e-mail: productcompliance@evansvanodine.co.uk

EU Supplier:
Evans Vanodine Europe
6-9 Trinity Street, Dublin 2.
D02 EY47.
Republic of Ireland.

1.4. Emergency telephone number

Emergency telephone New Safety Data Sheets - 01772 322 200 - Mon to Thur 8.30am to 4.30pm - Fri 8.30am to 1.30pm. (Also available 24/7 from our website www.evansvanodine.co.uk) For Technical Advice about this SDS - 01772 318 818 - Mon to Thu 8.30am to 4.45pm - Fri 8.30am to 1.30pm

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

Precautionary statements P102 Keep out of reach of children.
P301 IF SWALLOWED:
P313 Get medical advice/ attention.
P501 Dispose of contents/ container in accordance with local regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

LIFT RTU

SODIUM DODECYL BENZENE SULPHONATE **0.1-1%**

CAS number: 68411-30-3 EC number: 270-115-0

Classification
Acute Tox. 4 - H302
Skin Irrit. 2 - H315
Eye Dam. 1 - H318
Aquatic Chronic 3 - H412

SODIUM METASILICATE **0.1-1%**

CAS number: —

Classification
Skin Corr. 1B - H314
Eye Dam. 1 - H318

2-BUTOXYETHANOL **0.1-1%**

CAS number: 111-76-2 EC number: 203-905-0

Classification
Acute Tox. 4 - H302
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Skin Irrit. 2 - H315
Eye Irrit. 2 - H319

SODIUM CUMENE SULPHONATE **0.1-1%**

CAS number: 15763-76-5 EC number: 239-854-6

Classification
Eye Irrit. 2 - H319

SODIUM HYDROXIDE **<0.1%**

CAS number: 1310-73-2 EC number: 215-185-5 REACH registration number: 01-2119457892-27-xxxx

Spec Conc Limits :- Skin Corr. 1A (H314) >= 5 %, Skin Corr. 1B (H314) >=2% <5 %, Skin Irrit. 2 (H315) >=0.5%<2%, Eye Irrit. 2 (H319) >=0.5% <2%

Classification
Met. Corr. 1 - H290
Skin Corr. 1A - H314
Eye Dam. 1 - H318

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The ingredients are present in non-hazardous concentrations.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Unlikely route of exposure as the product does not contain volatile substances. If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Do not induce vomiting. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Wash with plenty of water.
Eye contact	Rinse immediately with plenty of water. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known. But - May cause discomfort if swallowed.
Skin contact	No specific symptoms known. But prolonged or excessively repeated skin contact could lead to removal of natural oils from skin.
Eye contact	No specific symptoms known. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Thermal decomposition or combustion products may include the following substances: Irritating gases or vapours.

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	No special protective clothing. (See Sec 8)

6.2. Environmental precautions

Environmental precautions	Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Small Spillages: Flush away spillage with plenty of water. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions No specific recommendations.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container in a cool, well-ventilated place. Store away from the following materials: Oxidising materials.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description See Product Information Sheet & Label for detailed use of this product.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³
Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³
Sk

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit.
Sk = Can be absorbed through skin.

8.2. Exposure controls

Appropriate engineering controls Not relevant.

Eye/face protection No specific eye protection required during normal use.

Hand protection No specific hand protection noted, but protection for the skin is advisable to prevent removal of natural oils from skin.

Other skin and body protection None required.

Respiratory protection Respiratory protection not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Clear. Colourless.

Odour Faint Solvent.

pH pH (concentrated solution): 12.0

Melting point -2°C

Initial boiling point and range 102°C @ 760 mm Hg

Flash point Boils without flashing.

Relative density 1.003 @ 20°C

Solubility(ies) Soluble in water.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Reactions with the following materials may generate heat: Strong acids.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions See sections 10.1,10.4 & 10.5

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects We have not carried out any animal testing for this product. Any ATE figures quoted below are from Toxicity Classifications that have been carried out using ATE (Acute Toxicity Estimate) Calculation Method using LD50 or ATE figures provided by the Raw Material Manufacturer.

Other health effects Low oral toxicity, but ingestion may cause irritation of the gastro-intestinal tract.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity We have not carried out any Aquatic testing, therefore we have no Aquatic Toxicity Data specifically for this product. The Aquatic Toxicity Data, where provided by the raw material manufacturer for ingredients with aquatic toxicity, can be made available on request.

12.2. Persistence and degradability

Persistence and degradability The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

LIFT RTU

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Discharge used solutions to drain. Small amounts (less than 5 Litres) of unwanted product may be flushed with water to sewer. Larger volumes must be sent for disposal by approved waste contractor. Consign empty container to normal waste.

SECTION 14: Transport information

General Not classified for Transport.

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Safety Data Sheet prepared in accordance with REACH Commission Regulation (EU) No 2015/830 (which amends Regulation (EC) No 453/2010 & 1907/2006).
The product is as classified under GHS/CLP- Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures.
Ingredients are listed with classification under GHS/CLP - Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out as not applicable as this product is a mixture.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.
ATE: Acute Toxicity Estimate.
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
GHS: Globally Harmonized System.
Spec Conc Limits = Specific Concentration Limits.

Classification abbreviations and acronyms
Acute Tox. = Acute toxicity
Aquatic Chronic = Hazardous to the aquatic environment (chronic)
Eye Dam. = Serious eye damage
Eye Irrit. = Eye irritation
Met. Corr. = Corrosive to metals
Skin Corr. = Skin corrosion
Skin Irrit. = Skin irritation

Key literature references and sources for data Material Safety Data Sheet, Miscellaneous manufacturers. CLP Class - Table 3.1 List of harmonised classification and labelling of hazardous substances. ECHA - C&L Inventory database.

LIFT RTU

Classification procedures according to Regulation (EC) 1272/2008	Calculation Method.
Revision comments	Safety Data Sheet amended in accordance with REACH Commission Regulation (EU) No 2015/830 amendment. (Changes to Sections 2,3,15&16)
Revision date	01/08/2017
Revision	6
SDS status	The Hazard Statements listed below in this Section No 16 relate to the Raw Materials (Ingredients) in the Product (as listed in Section 3) and NOT the product itself. For the Hazard Statements relating to this Product see Section 2.
Hazard statements in full	H290 May be corrosive to metals. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H412 Harmful to aquatic life with long lasting effects.